

MES-34 CONCRETE POLISHER

Handle

Adjusts to the operator's height for increased comfort and reduced fatigue.

Safety trigger

Stops the machine when the operator lets go of the handle.

Direct drive motors

3 x 5 HP, 460V, 6 amp, 1725RPM.

Effectively uses polishing pads from 16 through 3000 grit.



Built in volt meter
Monitors electrical input.

Integrated electrical panel allows for easy access to circuit breakers and on-board power ports.



Polishing deck
Pivots backward for fast, safe and easy tool change.

SPECIFICATIONS

Order No:	219320
Motor:	5 HP; 3 Phase, 460V
Current:	6 AMPS
Speed:	1725 RPM
Rear Wheels:	8"
Rear Casters:	3.5"
Vacuum Inlets:	Dual 2"
Dust Skirt:	4" Heavy Duty Rubber
Integrated Receptacles:	(2) 460V (1) 230V-277V
Pad Drivers:	(3) 12" Velcro Backed
Circuit Breakers:	(2) 460V 20amp (1) 230V-277V 10 amp

Optional Accessories:

DS-1220 Vacuum	214876
Order No:	214876
Vacuum Motor:	3 HP, Turbine, CFM: 180
Waterlift:	78"
Current:	208/230/460
Sound Level:	76dBA
Power Cord:	30 Ft. 18/3 Grounded Safety Yellow
Capacity:	9 gallon

Polishing production up to 5,000 square feet per grit per hour.

MADE IN THE **U.S.A.**

