## **SPS 35** Sump/Slurry Vacuum



# VACUUM, SEPARATE, AND RETURN, EFFICIENTLY AND EFFECTIVELY



### **Ideal Applications:**

- Oil and Chip Separation
- Coolant Transfer and Aeration
- Machine Shop Sump Cleaning Concrete Saw Slurry Collection

- Metal and Plastic Chip Collection
  Water Recovery from Pressure Washing
- Food Manufacturer Wash Down Recovery
- Automated Coolant Feed and **Evacuation System**







Collecting and separating chips has never been easier! With Ruwac's SumpPro Lite SPS 35 Sump Vacuum, chips and coolant are guickly collected and separated, reducing downtime and maintenance and allowing for increased production.

The SumpPro Lite features a compact design with heavy duty, locking casters and a full handlebar for complete portability. A top-hinged door allows quick access to a 4 gallon chip basket to easily empty collected chips, and a 2 inch, clear drain hose permits easy drainage of collected liquids. An optional return pump is also available to efficiently pump liquids for continued use or relocation. Constructed with compression cast composite modular housing, the SumpPro Lite is virtually indestructable and corrosion, dent and rust resistant, ensuring maximum longevity

and minimal maintenance.

Don't worry about spillage, the SumpPro Lite is equipped with positive closure float а assembly to automatically stop the vacuum when full and prevent overfilling. A full range of accessories and tools are available to customize the **SumpPro** Lite to your application.






Technical Data	SPS 35
Voltage	110*
Vacuum Pressure (Hg")	7.9
Air Movement (CFM)	112
Filter Area (gallon)	4 gallon
Capacity (gallon)	9 ğallon
Inlet (in.)	2"
Weight (lbs.)	110
L x Ŵ x Ĥ (in.)	32 x 20 x 50

For increased capacity, inquire about our SumpPro SPS250.

#### FEATURES



4 Gallon chip basket separates and collects chips from liquid while allowing easy disposal.



Large inlet allows maximum chip collection and hinged top door gives quick access to chip basket.



Compression cast composite housing is extremely durable and dent, corrosion and rust resistant.

Distributed by:



As an added safety mesasure, a positive closure float assembly prevents machine from overfilling.



\*220 volt single phase available

Specifications are subject to change without notice.

An external 2" discharge hose allows liquid collection to be drained to alternate locations.



Latta Equipment 330 E Hebron St Ste J Charlotte, NC 28273

Tel (704) 752-7944 Fax (704) 414-6811 www.WorkDustFree.com